

## USER INSTRUCTIONS

### CLEANOR 101

ELECTROLYTIC DEGREASER FOR GALVANIC

Colour : —

Use : **Bath**

Colour coordinates : L: —

a: —

b: —

#### Product description

CLEANOR 101 is a ready-to-use electrolytic degreasers specifically for the perfect degreasing of precious metals.

#### Operating conditions

| Parameter           | Average suggested value |
|---------------------|-------------------------|
| Treatment time      | 120 seconds             |
| Temperature         | 20 °C                   |
| Voltage             | 6.5 V                   |
| Current density     | 6.5 A/dm <sup>2</sup>   |
| Cathodic efficiency | —                       |
| Deposition speed    | —                       |
| Anodes              | Stainless Steel         |
| Agitation           | Moderate                |
| Ventilation         | Necessaria              |

#### Maintenance of plating bath

The degreasing consumption is strictly related to the quantity of articles you have cleaned. Normally we suggest to change the solution when is dirty with deposition on the bottom or when the current displayed on the rectifiers is the 30% less then initially with the same working voltage.

#### Safety Information

Please refer to the safety data sheets for any information regarding safety and disposal ( MSDS ).

## USER INSTRUCTIONS

### CLEANOR 101

ELECTROLYTIC DEGREASER FOR GALVANIC

Colour : —

Use : —

Colour coordinates : L: —

a: —

b: —

#### Related products

| Cod.Articles | Description   | Colour | Packaging |
|--------------|---|--------|-----------|
| SG011901     | <b>CLEANOR 101</b> (electrolytic degreaser ready to use ) | —      | 1 L       |
| SG011905     | <b>CLEANOR 101</b> (electrolytic degreaser ready to use ) | —      | 5 L       |